

EXT. KU-BAND BUC

Extended KU Block Up Converter



Upcom Technologies' line of Extended Ku Solid State Block Up Converters fills a market need for a reliable low-cost satellite amplifier and converter package in non-standard frequencies. It can be used for video, data and voice applications over satellite. High reliability is a key factor in this design allowing for years of maintenance free operation field proven in the most remote areas of the world.

- **SSPA BASED**
- **AC UNIVERSAL POWER INPUT**
- **MODULAR DESIGN**
- **AVAILABLE IN 25W, 32W, 40W, 50W, 80W and 100W**
- **2 YEAR WARRANTY!**

Model	UC-25XKU	UC-32XKU	UC-40XKU	UC-50XKU	UC-80XKU	UC-100XKU
Output Power (PSAT)	25W	32W	40W	50W	80W	100W
Gain, dB min.	73dB	73dB	76dB	76dB	76dB	77dB
Power Consumption	250W	350W	600W	610W	650W	650W

Output Range:	13.75-14.50GHz
Input Range:	950 to 1800 MHz
Gain Flatness over 50MHz:	+/-1.0dB max. at room temperature
Gain Flatness full band	+/-2.5dB max. at room temperature
Gain Variation	+/-1.5dB max. at operating temperature
Input VSWR:	2.0:1 max.
Output Return Loss:	-17dB max.
Spurious at Rated Power:	-50dBc max
Third Order IMD:	-30dBc max @ 7dB back off
Output Phase Noise:	@1KHz : -75dBc/Hz @ 10KHz : -80dBc/Hz @ 100KHz : -90dBc/Hz
IF Input (L-band):	Type N Connector
RF Output (Ku-Band):	WR-75 Grooved

M&C:	RS-485/RS-232 or analog
Altitude:	Up to 10,000ft
Temperature:	Operating Temperature: -40° to +55°C Storage Temperature: -55° to +85°C
Humidity:	98%
Shock and Vibration:	Equal to mobile van or stationary rack.
AC Power:	85VAC to 220VAC 50/60Hz

UPCOM Technologies Inc.

2033 Gateway Place, 5th Floor, San Jose, California 95110

Phone: 1.408.329.4158 • Fax: 1.408.329.4159 • E-mail: sales@upcom.com

web : www.upcom.com

