

# KU-BAND BUC

## Ku-band Block Up Converter



Upcom Technologies' line of Solid State Block Up Converters fills a market need for a reliable low-cost all-in-one satellite amplifier and converter package. It can be used for video, data and voice applications over satellite. High reliability is a key factor in this design allowing for years of maintenance free operation field proven in the most remote areas of the world.

- SSPA BASED
- AC UNIVERSAL POWER INPUT
- INTERNAL OR EXTERNAL 10MHz (OPTION)
- AVAILABLE IN 16W, 25W, 40W, 50W, 80W and 100W
- 2 YEAR WARRANTY!

Model	UC-16KU	UC-25KU	UC-40KU	UC-50KU	UC-80KU	UC-100KU
Output Power (PSAT)	16W	25W	40W	50W	80W	100W
Gain, dB min.	70dB	70dB	80dB	80dB	80dB	80dB
Power Consumption	250W	350W	600W	1000W	1200W	1300W

<b>Output Range:</b>	14.00 to 14.50 GHz (others optional)	<b>M&amp;C:</b>	RS-485/RS-232 or analog
<b>Input Range:</b>	950 to 1450 MHz	<b>Altitude:</b>	Up to 10,000ft
<b>Gain Flatness over 50MHz:</b>	+/-1.0dB max. at room temperature	<b>Temperature:</b>	Operating Temperature:-40° to +55°C Storage Temperature: -55° to +85°C
<b>Gain Flatness full band</b>	+/-2.5dB max. at room temperature	<b>Humidity:</b>	100% considering 2" rain per hour
<b>Gain Variation</b>	+/-1.5dB max. at operating temperature	<b>Shock and Vibration:</b>	Equal to mobile van or stationary rack.
<b>Input VSWR:</b>	2.0:1 max.	<b>AC Power:</b>	85VAC to 220VAC 50/60Hz
<b>Output Return Loss:</b>	-17dB max.		
<b>Spurious at Rated Power:</b>	-50dBc max		
<b>Third Order IMD:</b>	-30dBc max @ 7dB back off		
<b>Output Phase Noise:</b>	@1KHz: -75dBc/Hz @ 10KHz: -80dBc/Hz @ 100KHz: -90dBc/Hz		
<b>IF Input (L-band):</b>	Type N Connector		
<b>RF Output (C-Band):</b>	WR-75 Grooved		

### UPCOM Technologies Inc.

2033 Gateway Place, 5th Floor, San Jose, California 95110

Phone: 1.408.329.4158 • Fax: 1.408.329.4159 • E-mail: sales@upcom.com

web : www.upcom.com

