

UC-IRD 2SD RECEIVER DECODER

DVB-S MPEG 2 SD ASI/SDI/IP

Upcom Technologies' line of Advanced Integrated Receivers are designed with ease of use and reliability in mind, for satellite digital TV content delivery applications with 4:2:0 video decoding, with digital and analog program outputs.



- DVB-S and IP Receiver
- MPEG-2 SD Decoder
- SDI/YPbPr/Balanced Audio/IP Outputs
- BISS Descrambler
- 2 CI Slots
- Compatible with: Conax, Cryptoworks, Irdeto, NDS, Mediaguard, SECA, Viaccess and more
- Teletext VBI, EBU, DVB and CC support

Inputs:	RF: DVB-S, QPSK	Controls:	Front Panel
Decoding:	MPEG-2 / SD / 4:2:0 NTSC & PAL	Altitude:	Up to 10,000ft
Digital Video Output:	SDI HDMI IP STREAMING ASI	Temperature:	Operating Temperature: 0° to +45°C Storage Temperature: -25° to +55°C
Analog Video Output:	Composite Component	Humidity:	10 to 75%
Analog Audio:	Balanced XLR	Shock and Vibration:	Equal to mobile van or stationary rack.
		AC Power:	85VAC to 265VAC 50/60Hz 50W
		Dimensions:	8"W 2"H 8"D @ 2lbs

UPCOM Technologies Inc.

2033 Gateway Place, 5th Floor, San Jose, California 95110
Phone: 1.408.329.4158 • Fax: 1.408.329.4159 • E-mail: sales@upcom.com
web : www.upcom.com

